

Model Specifications for Residential Applications

Model No.	Max. Flow Rate	Application	Inlet-Outlet Connections	Diameter	Length	Weight
I	3 GPH	Ice Makers	1/4" Compression	1 1/4"	4 7/8"	1 lb.
H	6 GPH	Humidifiers	1/4" Compression	1 1/4"	5 3/8"	1.1 lb.
GH	5 GPM	Sprinkler-Lawn/Garden	Standard Garden Hose Fittings	1 1/2"	6"	2 lbs.
R	6 GPM	Water Heaters	3/4" FNPT	1 3/4"	9"	3 lbs.
RX	9 GPM	Mainline: Homes w/ up to 1 1/2 baths	1" FNPT	2 1/4"	9 1/4"	5 lbs.
RX-Special	12 GPM	Mainline: Homes w/ up to 3 1/2 baths	1" FNPT	2 1/4"	13"	7 lbs.
RES	20 GPM	Mainline: Homes	1" FNPT	2 1/4"	15"	8 lbs.
R-150	35 GPM	Mainline: Home	1 1/2" FNPT	2 5/8"	15 3/4"	13 lbs.
R-200	50 GPM	Mainline: Home	2" FNPT	3"	16 1/4"	15 lbs.
GT-1	4 GPM	Geo-thermal systems	1/2" FNPT	1 1/2"	12 5/8"	4 lbs.
GT-2	8 GPM	Geo-thermal systems	3/4" FNPT	1 3/4"	13"	5 lbs.
GT-3	15 GPM	Geo-thermal systems	1" FNPT	2 1/4"	13 1/2"	7 lbs.
SPS-20-P	20 GPM	Pool/Spa	1" PVC Socket	2 1/4"	9 3/4"	4 lbs.
SPS-45-P	45 GPM	Pool/Spa	1 1/4" PVC Socket	3"	15 3/8"	8 lbs.
SPS-75-P	75 GPM	Pool/Spa	1 1/2" PVC Socket	3 1/16"	14 7/8"	8 lbs.
SPS-100-P	100 GPM	Pool/Spa	2" PVC Socket	3 1/4"	15"	10 lbs.
SPS-150-P	150 GPM	Pool/Spa	2 1/2" PVC Socket	4 5/16"	19 1/4"	19 lbs.
SPS-200-P	200 GPM	Pool/Spa	3" PVC Socket	5 7/16"	21"	21 lbs.
SPS-250-P	250 GPM	Pool/Spa	4" PVC Socket	6 1/4"	23"	36 lbs.