

Model Specifications for Food Service & Other Commercial Applications

Model No.	Capacity	Connections	Diameter	Length	Weight
C-5	3 GPH	1/4" Compression	1 1/4"	4 7/8"	1 lb.
C-10	6 GPH	1/4" Compression	1 1/4"	5 3/8"	1.1 lb.
C-25	15 GPH	1/4" Compression	1 1/4"	7 5/8"	1.5 lb.
C-50	30 GPH	1/4" Compression	1 1/4"	8 5/8"	1.7 lb.
C-75	45 GPH	3/8" Compression	1 1/4"	9 5/8"	2 lbs.
C-100	1 GPM	3/8" Compression	1 1/4"	11 5/8"	2.2 lbs.
C-200	2 GPM	1/2" Compression	1 1/4"	11 7/8"	2.5 lbs.
RT-500	4 GPM	1/2" FNPT	1 1/2"	12 5/8"	4 lbs.
RT-750	8 GPM	3/4" FNPT	1 3/4"	13"	5 lbs.
RT-1000	15 GPM	1" FNPT	2 1/4"	13 1/2"	7 lbs.
SF-1250	30 GPM	1 1/4" Flange	6"	19 3/8"	27 lbs.
SF-1500	50 GPM	1 1/2" Flange	7 1/2"	23 3/4"	51 lbs.
SF-2000	75 GPM	2" Flange	8 1/2"	28"	68 lbs.
SF-2500	110 GPM	2 1/2" Flange	9"	31"	82 lbs.
SF-3000	175 GPM	3" Flange	10"	35 5/8"	117 lbs.
SF-4000	250 GPM	4" Flange	11"	39 3/4"	170 lbs.
SF-5000	350 GPM	5" Flange	13 1/2"	37 5/8"	308 lbs.
ACV-2	80 GPM	2" Flange	5 3/4"	14 1/4"	24 lbs.
ACV-2.5	120 GPM	2 1/2" Flange	6"	16 1/4"	29 lbs.
ACV-3	180 GPM	3" Flange	10"	26 3/8"	90 lbs.
ACV-4	300 GPM	4" Flange	11"	29 1/2"	127 lbs.
ACV-5	500 GPM	5" Flange	13 1/2"	37 5/8"	268 lbs.
ACV-6	650 GPM	6" Flange	16"	40"	409 lbs.
ACV-8	900 GPM	8" Flange	19"	42"	598 lbs.
ACV-10	1200 GPM	10" Flange	21"	52"	744 lbs.
ACV-12	2000 GPM	12" Flange	23 1/2"	54"	1021 lbs.
ACV-14	3000 GPM	14" Flange	25"	56"	1246 lbs.
ACV-16	3800 GPM	16" Flange	27 1/2"	66"	1581 lbs.
ACV-18	5000 GPM	18" Flange	32"	66"	2163 lbs.
ACV-20	6400 GPM	20" Flange	34 1/4"	74"	2497 lbs.
ACV-24	8000 GPM	24" Flange	38 3/4"	74"	3303 lbs.

